

RECEPTORES

US-902DC US-8001DC

Receptores para microfonía inalámbrica en banda UHF, con *diversity* y selección de hasta 16 frecuencias en la banda de 863 a 865 Mhz.



	US-902DC	US-8001DC
Rango de frecuencias	863 ~ 865 MHz, UHF	863 ~ 865 MHz, UHF
Capacidad	2 micrófonos	1 micrófono
Alimentación	12 V CC (adaptador), 500 mA	12 V CC (adaptador), 500 mA
Antena	Incorporadas / conectores BNC	Incorporadas
Salida de audio	-12 dB, sim (2 x XLR) asim (jack)	-12 dB, sim (XLR) asim (jack)
Selección de canales	Teclado y pantalla frontal	Conmutador frontal
Relación señal-ruido	Superior a 105 dB	Superior a 105 dB
Distorsión armónica total	Inferior al 0,6 % (a 1kHz)	Inferior al 0,6 % (a 1kHz)
Dimensiones (mm)	480 x 45 x 232 (1 u rack)	221 x 40 x 152
Respuesta en frecuencia	50 ~ 18.000 Hz, ±3 dB	50 ~ 18.000 Hz, ±3 dB

Distribuidor de antenas

UA-900



Antena de pared

UB-900



RECEIVERS

US-902DC US-8001DC

Receivers for wireless microphones in UHF band with diversity and selection of up to 16 frequencies in the band from 863 to 865 Mhz.



	US-902DC	US-8001DC
Frequency range	863 ~ 865 MHz, UHF	863 ~ 865 MHz, UHF
Capacity	2 microphones	1 microphone
Power supply	12 Vdc (adapter), 500 mA	12 Vdc (adapter), 500 mA
Aerial	BNC connectors/incorporated	Incorporated
Audio output	-12 dB, sym (2 x XLR) assym (jack)	-12 dB, sym (XLR) assym (jack)
Channel selection	Keyboard and front display	Front switch
Signal-to-noise ratio	Over 105 dB	Over 105 dB
Total harmonic distortion	Under 0.6% (at 1 kHz)	Under 0.6% (at 1 kHz)
Dimensions (mm)	480 x 45 x 232 (1 u rack)	221 x 40 x 152
Frequency response	50 ~ 18,000 Hz, ±3 dB	50 ~ 18,000 Hz, ±3 dB

Antenna distributor

UA-900



Wall antenna

UB-900

