

## Pupitre microfónico de zonas



### 4E-CMP

Pupitre microfónico de sobremesa con micrófono en flexo y 6 pulsadores. Permite el envío de mensajes en directo a un máximo de seis zonas de altavoces.

El equipo se conecta al equipo principal con cable FTP CAT5e o superior a una distancia de hasta 250 m, y puede encadenarse (entrada-salida) con otros pupitres microfónicos.



Nº de zonas	6
Pulsadores	de selección de zona, configurables
Alimentación	24 V CC (vía L-Net) / 50 mA máx
Respuesta en frecuencia	100 Hz ~ 12 kHz
Procesado de audio	Muestreo a 24 kHz, compresión ADPCM
Interfaz de red local (L-Net)	FTP CAT5e o superior, RJ45, hasta 250 m Hasta 8 pupitres por enlace L-Net (daisy-chain) Hasta 16 pupitres por sistema
Acabado	Acero y ABS
Montaje	Sobremesa y pared (soporte incluido)
Dimensiones	Base: 60 x 130 x 210 mm, flexo: 315 mm
Peso	520 g

## Zone microphone desk



### 4E-CMP

Tabletop microphone desk with gooseneck microphone and 6 buttons. It allows the sending of live messages to a maximum of six speaker zones.

The equipment is connected to the main equipment with FTP CAT5e or higher cable at a distance of up to 250 m, and can be chained (input-output) with other microphone desks.



Number of zones	6
Buttons (configurable)	zone selection
Power supply	24 V DC (via L-Net) / 180 mA max
Frequency response	100 Hz ~ 12 kHz
Audio processing	24 kHz sampling, ADPCM compression
Local network interface (L-Net)	FTP CAT5e or higher, RJ45, up to 250m Up to 8 desks per L-Net link (daisy-chain) Up to 16 desks per system
Finish	Steel and ABS
Mounting	Desktop and wall (support included)
Dimensions	Base: 60 x 130 x 210 mm, gooseneck: 315 mm
Weight	520 g